

IN THE CLAIMS:

1. (Currently Amended) A semiconductor device comprising:
peripheral electrodes formed on a periphery of a
semiconductor chip;

internal electrodes formed inside the peripheral electrodes
on the semiconductor chip; and

circuits formed in the semiconductor chip,

wherein the peripheral electrodes are connected to the
circuits by an internal line, and the internal electrodes are
connected to the circuits and the peripheral electrodes by the
internal line, said internal line being covered by an insulating
layer, and

wherein ~~the~~ a same signal is either an input and/or output
either to or from both ~~an~~ the internal electrode and the
peripheral ~~electrode~~ electrodes, and

wherein rewiring is connected to the peripheral electrodes,
or to the internal electrodes in the case of CSP packaging, and
a wire is connected to the peripheral electrodes in the case of
connecting to external terminals using wire bonding.

2. (Original) A semiconductor device according to Claim 1,
wherein the internal electrodes are smaller than the peripheral
electrodes.

3. (Original) A semiconductor device according to Claim 1, wherein the internal electrodes comprise at least one selected from the group consisting of a power supply terminal, a ground terminal, and a clock terminal.

4. (Previously Presented) A semiconductor device according to Claim 1, wherein the peripheral electrodes not connected to the internal electrodes are used as terminals for RF signals.

5. (Currently Amended) A semiconductor device comprising:
peripheral electrodes formed on a periphery of a
semiconductor chip;

internal electrodes formed inside the peripheral electrodes
on the semiconductor chip; and

circuits formed in the semiconductor chip,

wherein the peripheral electrodes are connected to the
circuits by an internal line covered by an insulating layer, the
internal electrodes are connected to the circuits and the
peripheral electrodes by the internal line, and the internal
electrodes are also connected to rewired lines, the rewired
lines formed above the internal electrodes with an insulating
layer therebetween, and at ends of the rewired lines formed area
array electrodes.

6. (Currently Amended) A semiconductor device comprising:
peripheral electrodes formed on a periphery of a
semiconductor chip;

internal electrodes formed inside the peripheral electrodes
on the semiconductor chip;

area array electrodes connected to selected one of the
peripheral electrodes and the internal electrodes and formed on
the semiconductor chip; and

circuits formed in the semiconductor chip,

wherein the peripheral electrodes are connected to the
circuits by an internal line covered by an insulating layer, the
internal electrodes are connected to the circuits and the
peripheral electrodes by the internal line, and the area array
electrodes comprise first area array electrodes connected to the
internal electrodes by rewired lines and second area array
electrodes connected to the peripheral electrodes by rewired
lines.

7. (Original) A semiconductor device according to Claim 6,
wherein the first area array electrodes comprise at least one
selected from the group consisting of a power supply terminal, a
ground terminal, and a clock terminal.

8. (Previously Presented) A semiconductor device according to Claim 6, wherein the second area array electrodes are used as terminals for RF signals.